

# 4/5 Gas Analyzer Technical Specification BTGS22

COMBINED GAS ANALYZER AND SMOKE METER



Easy to carry & Operate

Features Battery-based & Magnetic

Very Compact, Small in Size & Light in Weight

High Quality Indian Product with Latest Technology



## TECHNICAL SPECIFICATIONS

Measurement Parameter	Principle of Measurement	Specified Range	Accuracy vol	Accuracy %	Resolution
CO	NDIR	0-15%	±0.06%	±3%	0.001%
HC	NDIR	0-20000 PPM	±12 PPM	±5%	1 PPM
CO2	NDIR	0-20%	±0.4%	±4%	0.1%
O2	Electro-Chemical	0-21%	±0.1%	±3%	0.01%
OIL Temp	RTD	0-150°	±0.2°c	±0.3%	1. 0°c
NOX	Electro-Chemical (Opt.)	0-5000	25 PPM	±5%	1PPM
RPM	Battery Based	400-9999	10 RPM		1 RPM
	Magnetic Based	400-9999	10 RPM		1 RPM
LAMBDA		0-9.999			0.001
Power Supply	AC:230V /1Ph/50 - 60Hz ± 10% Adapter Through External Battery 12VDC ± 10%				
power consumption	36 W				
Warm UP Time	425 sec.				
Fuel Types	Petrol,CNG, LPG				
Operating Temperature	0-50°c pressure between 850 mBar an 1060 mBar , Humidity : 0-90% relative				
Response Time	10sec				
Measuring Gas	5 L/Min				
Display	128x64 graphical Lcd (3.60 mm Character Size)				
Remote Display	128x64 Graphical Lcd (3.60 mm Character Size) optional				
PC Compatible	RS 232 Cable & USB optional				
Printer	Thermal printer optional				
Keyboard	Membrane Keypad 12 keys				
Zero	Auto zero & Manuals Zero				
Gas Flow Rate	3.5 l/min. to 4.5 l/min				
Dimension	L 16.5 X B 9.5X H 10 Inch				
Weight	10.00 Kgs.				



## UTKAL ELECTRONICS

Plot No - 97/156/430, Khata No-43/161, Motiganj, Kasimabad,  
Sadar, Balasore, Odisha, 756003. Mob : 9810908619

Customer Care No. : +91 9827011539 E-mail : info@utkalelectronics.com

Website : www.utkalelectronics.com